



NOTES:

1. ALL FOOTINGS SHALL BE 520-C-2500 CONCRETE.
2. THE FOLLOWING ITEMS SHALL BE FURNISHED AND INSTALLED ONLY WHEN SHOWN ON THE PLANS OR CALLED FOR IN THE SPECIAL PROVISIONS:
 - A. BARBED WIRE
 - B. EXTENSION ARM
3. CHAIN LINK FENCE SHALL CONFORM TO THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION UNLESS SPECIFICALLY NOTED ON THIS DRAWING.
4. CHAIN LINK FENCE AND ALL FITTINGS SHALL BE BLACK 22 MIL PRESSURE - BONDED OR 7 MIL THERMALLY - FUSED VINYL COATED OVER 9 GAUGE ALUMINIZED STEEL CORE FABRIC PRIOR TO COATING. POSTS AND RAILS SHALL BE GALVANIZED STEEL PVC VINYL BONDED, 10 - 14 MIL (COLOR SHALL MATCH FABRIC).
5. CHAIN LINK FABRIC SHALL HAVE KNUCKLED FINISH ON TOP EDGE.

LEGEND ON PLANS

-X-O-X-X-O-X-

REVISION	BY	APPROVED	DATE
ORIGINAL		J.P. CASEY	06/92
UPDATE	KA	J. NAGELVOORT	01/12

CITY OF SAN DIEGO - STANDARD DRAWING

VINYL COATED CHAIN LINK FENCE

RECOMMENDED BY THE CITY OF SAN DIEGO STANDARDS COMMITTEE

H. Hadzi

1/31/2012

COORDINATOR R.C.E. 85271 DATE

DRAWING NUMBER

SDM-112