



**NOTES**

1. Posts to be structural grade redwood or pressure treated (with wood preservative) Douglas Fir, surfaced four sides; cross pieces to be 51mm (2") x 203mm (8") select grade Douglas Fir, surfaced four sides.
2. All exposed portions of barricades shall be painted with two coats of white exterior enamel over prime coat.
3. Connections shall be made with 10mm (3/8") x 152mm (6") galvanized lag screws with one (1) washer each.
4. Reflector sign fasteners to be 10mm (3/8") x 38mm (1 1/2") galvanized lag screws.  
 Reflector signs - California Type N. Size 457mm (18") x 457mm (18") - Yellow with nine (9) - 83mm (3 1/4") reflectors (center mount).
  - a. Reflectors shall be red for use on dead end streets, in all other cases they shall be yellow. Reflector material shall be plastic or other approved reflectorized material.
  - b. Sign material shall be aluminum alloy 6061-T6 or 5052-H38, aluminum thickness 1.6mm (0.063").
5. 1.8m (6') long hat section metal post per Caltrans Std. Plan A74-A optional for guard post.

**LEGEND ON PLANS**



Revision	By	Approved	Date
ORIGINAL		Kercheval	12/75
Add Metric		T. Stanton	03/03
Reviewed		T. Stanton	04/06

SAN DIEGO REGIONAL STANDARD DRAWING

**GUARD POST AND BARRICADE**

RECOMMENDED BY THE SAN DIEGO REGIONAL STANDARDS COMMITTEE

*T. Stanton* 3/10/2003  
 Chairperson R.C.E. 19246 Date

DRAWING NUMBER **M-9**